

TECHNICAL DATASHEET

Main specs	Unit	ALAN PIUMA 4-1
Weighting box capacity	Lt	30 or 45
Max filling weight per shot	gr	100 (a), 70(b)
Storage box capacity	Lt	1350
N. of weighting scales	#	4
Working / Filling position(s)	#	1
Injection system	-	injection by air
Injection tube diameter	Mm	50 and 18,5
Max machine output (4)	Fillings / h	550
Technical data		
Voltage	V	400
Phase(s)	-	3Ph+N+G
Frequency	Hz	50
Installed Power	Kw	3,5 - 20A
Power consumption (1)	Kw	2,9
Air pressure	bar	8
Working pressure	bar	6
Max air consumption (2)	Lt / min	300
Air consumption (3)	Lt / min	20 x # fillings / min
Noise	dB	<70
Weight	Kg	600
Dimensions	cm	180x200x(h)240
Environmental Conditions		
Altitude a.s.l.	m	<1000
Internal temperature max.	°C	35
Internal temperature min.	°C	5
Non-condensing humidity min	%	20
Non-condensing humidity max	%	90
Ideal temperature for working (for down)	°C	1
Ideal humidity (for down)	%	60-65
Service air specs		
Standard quality reference		Using ISO 8573-1 standard quality
Particles		Quality class 3
Water / Humidity		Quality class 4
Oil		Quality class 3
Technical Standard		
Machinery compliant to Directive		2006/42/CE
Equipment certification		CE
Low voltage Directive		2014/35/UE or equivalent UL/CSA norms
Electromagnetic Compatibility Directive		2014/30/UE or equivalent UL/CSA norms
Components		
Electrical components		SIEMENS
PLC/PC		SIEMENS
Weighting scale		HBM
Electric motor		MT Motori Elettrici (Italy)
Pneumatic components		SMC

BORSOI S.r.l.

Via Cal de Prade, 109 - 31029 Vittorio Veneto (TV) Italy

Tel. +39 0438 586864 - Fax +39 0438 501153

E-mail: info@borsoi.eu - www.borsoi.eu

Legend	
1	Based on normal working conditions. It depends on production output and material consumption
2	It is required only when air booster is activated continuously. The air booster is a special device installed on the machine for applying a 6-bar air directly to the injection nozzle in order to speed up, moving heavy filling materials or cleaning pipes at the end of the batch. In standard working condition is not used
3	This is the average air consumption (from 15 Lt/min to 25 Lt/ min) in normal working conditions. It depends by the injection time (and so by the filling dose weight) per every single filling. The overall machine consumption shall be obtained by multiply this number by the number of fillings (per minute or per hour)
4	The system output depends on filling weight, filling tolerance, on the filling material type and quality, comforter fabric type and quality, environmental conditions (relative humidity and temperature), electrostatic charge, production procedure and operator skills. To be confirmed after the above-mentioned factor confirmation Real output depends on operator time for moving the jacket frame from channel to channel
a	Indicative value for synthetic fibers
b	Indicative value for down feather (80/20)